

# T6

# TRIKKE™

BROUGHT TO YOU BY

# AOK™

The **Trikke T6** shares the **Trikke8** frame but features custom-designed 6-inch polyurethane wheels with sealed bearings for a super-smooth, nearly effortless ride. The handlebars are easily adjustable to the rider's height preference, and it collapses quickly for transport or storage. The **Trikke T6** has independent rear brakes, and is constructed to our exacting specifications from aircraft-grade aluminum. The **Trikke 6** is well suited for the street and pavement, and can be enjoyed by both kids and adults. Includes a free video owner's manual and tool kit.

## specs

### Rider weight Limit

91 kg ( 200 lbs.)

### Vehicle weight

7.7 kg ( 17 lbs.)

### Frame material

al 6061 T6

### Finish

hi polishing

### Wheel size

PU/PP 150 mm ( 6in.)

### Brake system

dual rear independent, cable, hand actuated, canty-lever pad on the tyre

## Dimensions ready-to-ride

### Height

915-1040 mm ( 36-41 in.)

### Length

1055 mm ( 41.5 in.)

### Handlebar Width

610 mm ( 24 in.)

### Stance Width

550 mm ( 21 in.)

## Dimensions folded

### Height

200 mm ( 8 in.)

### Length

1000 mm ( 39.5 in.)

### Width

310 mm ( 12 in.)



# T8

# TRIKKE™

BROUGHT TO YOU BY

# AOK™

The new **Trikke T8 Convertible** can mount both polyurethane and custom 8.5 inch pneumatic tyres for the ultimate in performance flexibility.

The handlebars are easily adjustable to the rider's height preference, and it collapses quickly for transport or storage.

The **Trikke T8 Convertible** has independent rear brakes, and is constructed to our exacting specifications from aircraft-grade aluminum.

Tuned perfectly for a blend of speed, traction, shock absorption and durability, it's the high performance adult ride for comfort, fitness and deep carving fun.

## specs

### Rider weight Limit

114 kg ( 250 lbs.)

### Vehicle weight

10.0 kg ( 22 lbs.)

### Frame material

al 6061 T6

### Finish

epoxi painted

### Wheel size

PU/PP 200 mm ( 8in.)  
or alloy wheel /air tire 8.5 x 2 in.

### Brake system

dual rear independent, cable,  
hand actuated, canty-lever pad on the tyre

## Dimensions ready-to-ride

### Height

1200-1400 mm ( 47-55 in.)

### Length

1180 mm ( 46.5 in.)

### Handlebar Width

670 mm ( 26.5 in.)

### Stance Width

600 mm ( 23.5 in.)

## Dimensions folded

### Height

290 mm ( 11.5 in.)

### Length

1345 mm ( 53 in.)

### Width

375 mm ( 15 in.)



# 12

## ROADSTER

# TRIKKE™

BROUGHT TO YOU BY



The **Trikke 12 Roadster** with its customized, high-pressure pneumatic tyres and disc brakes eats up bad road and pushes the edge of the **T8** carving envelope times 10. Carve deeper and ride harder with confidence and control, and tackle hills like a giant slalom skier tackles the mountain.

Perfect for athletes wanting to combine a fast and exhilarating ride with excellent cross-training for endurance, balance, agility and strength. Also, because of its larger wheels and heavier frame, you'll find that it takes less turns to keep your speed – essential for anyone interested in long distance carving. **It's not for the faint of heart.**

### specs

#### Rider weight Limit

114 kg ( 250 lbs.)

#### Vehicle weight

13.6 kg ( 30 lbs.)

#### Frame material

al 6061 T6

#### Finish

epoxi painted

#### Wheel size

alloy wheel / air tyre  
12.1/2 x 2.1/4" ( 305 mm)

#### Brake system

dual rear independent, cable, disc

### Dimensions ready-to-ride

#### Height

1320-1440 mm ( 52-56.75 in.)

#### Length

1400 mm ( 55 in.)

#### Handlebar Width

700 mm ( 27.5 in.)

#### Stance Width

615 mm ( 24 in.)

### Dimensions folded

#### Height

370 mm ( 14.5 in.)

#### Length

1600 mm ( 63 in.)

#### Width

490 mm ( 19.25 in.)

